



TAMMSCOAT CRSE 4159 (SW6253) 5 GL PL

Version 1.
REVISION DATE: 10/09/2007

Print Date 11/07/2007

14808-60-7	Crystalline Silica (Quartz)/ Silica Sand
1897-45-6	Chlorothalonil
50-00-0	Formaldehyde
1333-86-4	Carbon Black

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum
1 = Slight
2 = Moderate
3 = Serious
4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists
 CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
 DOT - Department of Transportation
 DSL - Domestic Substance List
 EPA - Environmental Protection Agency
 HMIS - Hazardous Materials Information System
 IARC - International Agency for Research on Cancer
 MSHA - Mine Safety Health Administration
 NDSL - Non-Domestic Substance List
 NIOSH - National Institute for Occupational Safety and Health
 NTP - National Toxicology Program
 OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit
 RCRA - Resource Conservation and Recovery Act
 RTK - Right To Know
 SARA - Superfund Amendments and Reauthorization Act
 STEL - Short Term Exposure Limit
 TLV - Threshold Limit Value
 TSCA - Toxic Substances Control Act
 TWA - Time Weighted Average
 V - Volume
 VOC - Volatile Organic Compound
 WHMIS - Workplace Hazardous Materials Information System

**TAMMSCOAT CRSE 4159 (SW6253) 5 GL PL**

Version 1.

Print Date 11/07/2007

REVISION DATE: 10/09/2007

SECTION 15 - REGULATORY INFORMATION**North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

OSHA Hazardous Components :

Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
Titanium dioxide	13463-67-7
Ammonium hydroxide	1336-21-6
Formaldehyde	50-00-0

OSHA Status: Considered : Irritant
hazardous based on the : Carcinogen
following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 54 g/l
exempt solvent)
VOC Method 310 : 2 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

U.S. State Regulations:MASS RTK Components : Crystalline Silica (Quartz)/ Silica Sand 14808-60-7
Titanium dioxide 13463-67-7
Formaldehyde 50-00-0Penn RTK Components : Crystalline Silica (Quartz)/ Silica Sand 14808-60-7
Water 7732-18-5
Acrylic Polymer NJ TSRN# 51721300-5797P
Titanium dioxide 13463-67-7
Amorphous silicon dioxide NJ TSRN# 51721300-5881P
Propylene glycol 57-55-6NJ RTK Components : Crystalline Silica (Quartz)/ Silica Sand 14808-60-7
Water 7732-18-5
Acrylic Polymer NJ TSRN# 51721300-5797P
Titanium dioxide 13463-67-7
Amorphous silicon dioxide NJ TSRN# 51721300-5881P

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:

**TAMMSCOAT CRSE 4159 (SW6253) 5 GL PL**

Version 1.

Print Date 11/07/2007

REVISION DATE: 10/09/2007

Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: 32 °F, 0 °C
Boiling point/range	: 212 °F, 100 °C
Water solubility	: Soluble
Specific Gravity	: 1.6
% Volatile Weight	: 26.6 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Strong acids.Strong bases.
Stability	: Stable
Hazardous polymerization	: Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Propylene glycol, CAS-No.: 57-55-6 Acute oral toxicity (LD-50 oral)	30,000 mg/kg (Rat) 18,000 mg/kg (Rabbit) 19,000 mg/kg (Dog) 23,900 - 31,800 mg/kg (Mouse) 18,400 - 196,000 mg/kg (Guinea pig)
Ammonium hydroxide, CAS-No.: 1336-21-6 Acute oral toxicity (LD-50 oral)	350 mg/kg (Rat)
Formaldehyde, CAS-No.: 50-00-0 Acute oral toxicity (LD-50 oral)	800 mg/kg (Rat) 260 mg/kg (Guinea pig) 100 mg/kg (Rat) 42 mg/kg (Mouse)
Acute inhalation toxicity (LC-50)	0.82 mg/l for 30 min (Rat) 0.48 mg/l for 4 h (Rat) 0.414 mg/l for 4 h (Mouse) 0.4 mg/l for 2 h (Mouse)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Dispose of in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:
NOT REGULATED

**TAMMSCOAT CRSE 4159 (SW6253) 5 GL PL**

Version 1.

Print Date 11/07/2007

REVISION DATE: 10/09/2007

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**Personal protection equipment**

- Respiratory protection : Not required under normal conditions of use. Wear appropriate, NIOSH/MSHA approved respirator with combination particulate filter and vapor/gas removing cartridge when the ventilation is not adequate or if it is necessary to abrade or grind surfaces coated with this product.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing. Use rubber apron and overshoes.
- Protective measures : Other equipment not normally required. Use professional judgment in the selection, care, and use.
- Engineering measures : Not required under normal conditions of use. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA:	0.1 mg/m3	Respirable.
		OSHA TWA:	0.3 mg/m3	Total dust.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	0.025 mg/m3	Respirable fraction.
Titanium dioxide	13463-67-7	ACGIH TWA:	10 mg/m3	
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Ammonium hydroxide	1336-21-6	ACGIH TWA:	25 ppm	
		ACGIH STEL:	35 ppm	
		OSHA PEL:	35 mg/m3	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Liquid
- Color : Light Gray
- Odor : Slight Ammonia
- pH : 9 - 10
- Vapour pressure : Not available.

**TAMMSCOAT CRSE 4159 (SW6253) 5 GL PL**

Version 1.

Print Date 11/07/2007

REVISION DATE: 10/09/2007

Propylene glycol	57-55-6	1.0 - 5.0
Ammonium hydroxide	1336-21-6	<0.1
Formaldehyde	50-00-0	<0.1

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	:	Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for 15 minutes. If irritation persists, get medical attention.
Skin contact	:	Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Get medical attention. Do not induce vomiting.
Notes to physician	:	Not applicable.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point	:	Not available.
Method	:	Not applicable.
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	This product is not expected to burn under normal conditions of use.
Hazardous combustion products	:	Carbon monoxide and carbon dioxide can form. Smoke, fumes.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
Fire and explosion conditions	:	This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Transfer to appropriate container for disposal. Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal. Use appropriate protective equipment. Avoid contact with material.

SECTION 7 - HANDLING AND STORAGE

Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Keep from freezing. Do not use in confined or poorly ventilated areas. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a dry, ventilated warehouse location above freezing.

**TAMMSCOAT CRSE 4159 (SW6253) 5 GL PL**

Version 1.

Print Date 11/07/2007

REVISION DATE: 10/09/2007

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : TAMMSCOAT CRSE 4159 (SW6253) 5 GL PL
 Product code : TL22125054159

COMPANY : Euclid Chemical Company
 19218 Redwood Road
 Cleveland, OH 44110

Telephone : 1-800-321-7628
 Emergency Phone: : U.S. only: 1-800-424-9300
 International Users Call Collect: 1-703-527-3887

Product use : Coating

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Light Gray. Liquid. No serious effects anticipated under normal conditions of use. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : No serious effects anticipated under normal conditions of use.
 Eyes : Direct contact may cause mild irritation.
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.
 Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Long term overexposure to propylene glycol caused liver abnormalities, kidney damage in laboratory animals. Repeated excessive ingestion may cause central nervous system effects. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	40.0 - 70.0
Water	7732-18-5	15.0 - 40.0
Acrylic Polymer	NJ TSRN# 51721300-5797P	7.0 - 13.0
Titanium dioxide	13463-67-7	5.0 - 10.0
Amorphous silicon dioxide	NJ TSRN# 51721300-5881P	5.0 - 10.0